

DURACELL®

TECHNICAL DATA SHEET

Type no.	DA 40B
Article no.	013540250801
EAN/GTIN no.	9005753085893
Application	Starter battery
Electrical data	
Rated voltage	12V
Rated capacity	40 Ah (K20)
Cold start current	330 A (EN)
Dimensions and weights	
Box	B19
Length max.	187mm
Width max.	137mm
Box height max.	204mm
Total height max.	226mm
Battery weight	Ca. 9,5 kg (+/- 5 %)
Electrolyte density	Approx. 1,28 kg/l
Electrolyte	Diluted sulphuric acid
Items/pallet	96
Pallet ID	Euro pallet
Items per layer	32
Features	
Base hold-down	B01
Layout	0
Terminal	3
Separator	PE envelope separator
Degassing	Battery with central degassing
Flame arrester	Integrated
Performance identification	W4 - C2 - V2 - E1
Maintenance ¹⁾	
Water consumption	W4
Refill water	Distilled or demineralised (DIN 43530)
Self-discharge	Approx. 3 % per month
Charging current	Approx. 1/10 of the rated capacity
Charging voltage ²⁾	max. 14,8 V



¹⁾ All the listed values relate to room temperature +25° C

²⁾ Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

