

DURACELL®

TECHNICAL DATA SHEET

| | |
|--------------------------------|------------------------------------|
| Type no. | DE 80 AGM |
| Article no. | 016580010801 |
| EAN/GTIN no. | 9005753086104 |
| Application | Starter battery start-stop |
| Electrical data | |
| Rated voltage | 12V |
| Rated capacity | 80 Ah (K20) |
| Cold start current | 800 A (EN) |
| Dimensions and weights | |
| Box L4 | |
| Length max. | 315mm |
| Width max. | 175mm |
| Box height max. | 190mm |
| Total height max. | 190mm |
| Battery weight | Ca. 24,0 kg (+/- 5 %) |
| Electrolyte density | Approx. 1,32 kg/l |
| Electrolyte | Diluted sulphuric acid |
| Items/pallet | 56 |
| Pallet ID | Euro pallet |
| Items per layer | 14 |
| Features | |
| Base hold-down | B13 |
| Layout | 0 |
| Terminal | 1 |
| Separator | AGM separator |
| Degassing | Battery with central degassing |
| Flame arrester | Integrated |
| Performance identification | W5 - C2 - V3 - M3 (E4) |
| Maintenance ¹⁾ | |
| Water consumption | W5 |
| Refill water | Absolutely maintenance-free |
| Self-discharge | Approx. 3 % per month |
| Charging current | Approx. 1/20 of the rated capacity |
| Charging voltage ²⁾ | max. 14,8 V |



1) All the listed values relate to room temperature +25° C

2) Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

